Telephone: 01992 702475
Fax: 01992 702489
Email: Sales@Inghampaper.co.uk

DATE: 12.05.2022

## SPECIFICATION SHEET TOPBAKE - DOUBLE SIDED SILICONE VEGETABLE PARCHMENT

Topbake is a two sided silicone coated bleached vegetable parchment.

## Typical end-use:

For all bakery release applications together with frozen food, food interleave and industrial uses. Recommended process temperature up to 220°C.

## **Approvals:**

The mill is certified according to BRC Global Standard for Packaging Materials.

All raw materials and additives used in production comply with main food regulations.

Topbake is approved for direct contact with food by the FDA (USA), BGVV (Germany) and complies with Regulation (EC) 1935/2004 on materials and articles in contact with food.

PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE
Grammage (tolerance ±5%)	ISO 536	g/m²	45
Caliper	ISO 534	μ	59
Breaking Load MD	ISO 1924	daN/15mm	5.5
CD			3.5
Elongation MD	ISO 1924	%	1.8
CD			13
Dry Burst Index	ISO 2758		4
Water absorptiveness – Cobb60	ISO 535	g/m²	14

## **MIGRATION TEST RESULTS**

**Analysis Conditions:** 

MPPO (Tenax) Contact Temperature: 175°C

Time: 2 hours

MPPO mg/dm2 <2

Prepared by N. Rehman Ref STPB45—RM 12.05.22