DATE: 13.03.2015

Email: Sales@Inghampaper.co.uk

SPECIFICATION SHEET TOPBAKE - DOUBLE SIDED SILICONE VEGETABLE PARCHMENT

Topbake is a two sided silicone coated bleached vegetable parchment.

Typical end-use:

For all bakery release applications together with frozen food, food interleave and industrial uses. Recommended process temperature 220°C to 250°C.

Approvals:

The mill is certified according to ISO 9001:2008 and BRC/IoP.

Enfield, EN3 7FL

All raw materials and additives used in production comply with main food regulations.

Topbake is approved for direct contact with food by the FDA (USA), BGVV (Germany) and complies with Regulation (EC) 1935/2004 on materials and articles in contact with food.

| PROPERTY | TEST METHOD | UNIT | TYPICAL VALUE |
|-------------------------------|-------------|--------|---------------|
| Grammage (tolerance ±5%) | STM88 | g/m² | 45 |
| Thickness (tolerance ±10%) | STM44 | μ | 56 |
| Tensile strength | STM43 | N/15mm | 64 |
| Extension at break | | % | 1.9 |
| Burst Strength | STM41 | kPa | 180 |
| Tearing strength | STM42 | mN | MD 200 CD 240 |
| Water absorptiveness – Cobb60 | STM37 | g/m² | 12-15 |

MIGRATION TEST

| UNIT | TEST METHOD | VALUE |
|------|-------------|-------|
| 1 -4 | W I 15 | 1 |